
Our company's main products include external turning tools, internal turning tools of M,P,D,S,W,C type and threading tools, parting and grooving tools, indexable milling tools, drilling tools. At the same time, we can also undertake all types of non-standard tools.


Based on the excellent design, top-class CNC center, accurate testing equipment and perfect management process, Sant series' quality is always in the leading level. Since the establishment of our company we has always insisted: "United and Innovative, Honest and Pragmatic, Pioneering for progress, Pursuiting win-win outcomes". We've established good cooperation relationship with many large and medium-size enterprises and dealers all over the world. We'll work hard together persistently to support high-quality products and satisfactory service for all the customers!















FM E 03-100-B 32






Cuttin	g Ed	ge L	eng	th	(m	m)
		Shap	e of	Blac	de	
	С	D	R	S	Т	L
5.556	_	_	_	_	09	_
6.350	06	07			11	_
9.525	09	11	09	09	16	_
12.700	12	15	12	12	22	_
15.875	16	19	15	15	27	
19.050	19	_	19	19	33	_
25.400	25		25	25	44	25









Face Milling tool Kr:45°











Type of Milling Tools

	_	Sto	ck		Dim	ension	(mm)		Tooth	Adapter	Weight (kg)
	Type	R	٦	ØD	ØD1	ød	L	apmax	Z	Mapter	
FMA01	-050-A22-SE12-04	•	Δ	50	61	22	40	6	4	Α	0.3
	-063-A22-SE12-05	A	Δ	63	74	22	40	6	5	Α	0.5
	-080-A27-SE12-06	A	Δ	80	91	27	50	6	6	Α	1.2
	-100-B32-SE12-07	A	Δ	100	107	32	50	6	7	В	1.2
	-125-B40-SE12-08	A	Δ	125	136	40	63	6	8	В	2.6
	-160-B40-SE12-10	A	Δ	160	170	40	63	6	10	В	4.3
	-200-C60-SE12-12	A	Δ	200	210	60	63	6	12	С	7.6
	-250-C60-SE12-14	A	Δ	250	260	60	63	6	14	С	13.5
	-315-D60-SE12-18	Δ	Δ	315	325	60	70	6	18	D	20.8

∆Stock △ Order

Spare Parts


Diameter	Applicable Insert	insert screw	Shim	shim screw	Wrench	Wrench
ØD				Cultu		
Ø50 -Ø100		L60M3.5×10		_	T.15T	_
Ø125-Ø315	SE□T12T3	L60M3.5×10	S13BS	SM5×7XA	T15T	S4

Face Milling tool Kr:45°









Type of Milling Tools

_ ,1											
	Type	Stock Dimension (mm)				Tooth	Adapter	Weight			
	1 y p c		L	ØD	ØD1	ød	L	apmax	Z	Transfer	(kg)
FMA02	-050-A22-SE12-03	•	Δ	50	61	22	40	6	3	Α	0.4
	-063-A22-SE12-04	•	Δ	63	74	22	40	6	4	Α	0.6
	-080-A27-SE12-04	•	Δ	80	91	27	50	6	4	Α	1.3
	-100-B32-SE12-05	•	Δ	100	107	32	50	6	5	В	1.3
	-125-B40-SE12-06	A	Δ	125	131	40	63	6	6	В	2.6

▲Stock △Order

Spare Parts

Diameter	Applicable Insert	insert screw	Wrench				
ØD ØD							
Ø50-Ø125		L60M3.5×10	T15T				
	SE□T12T3						
	0=271210						


Face Milling tool Kr:45°











Type of Milling Tools

		Sto	ck		Dim	ension	(mm)		Tooth	Adapter	Weight
	Туре	R	L	ØD	ØD1	ød	L	apmax	Z	nuuptei	(kg)
FMA03	-080-A27-SE12-04	•	Δ	80	103	27	50	5.5	4	А	1.8
	-100-B32-SE12-05	•	Δ	100	122	32	50	5.5	5	В	2.4
	-125-B40-SE12-06	•	Δ	125	147	40	63	5.5	6	В	4.4
	-160-B40-SE12-08	•	Δ	160	181	40	63	5.5	8	В	6.4
	-200-C60-SE12-10	•	Δ	200	221	60	63	5.5	10	С	8.5
	-250-C60-SE12-12	•	Δ	250	270	60	63	5.5	12	С	14.1
	-315-D60-SE12-15	Δ	Δ	315	353	60	63	5.5	15	D	22.2
	-080-A27-SE15-04	A	Δ	80	103	27	50	7.5	4	Α	1.7
	-100-B32-SE15-05	A	Δ	100	122	32	50	7.5	5	В	2.3
	-125-B40-SE15-06	•	Δ	125	147	40	63	7.5	6	В	4.2
	-160-B40-SE15-08	A	Δ	160	181	40	63	7.5	8	В	6.1
	-200-C60-SE15-10	•	Δ	200	221	60	63	7.5	10	С	8.3
	-250-C60-SE15-12	•	Δ	250	270	60	63	7.5	12	С	13.6
	-315-D60-SE15-15	•	Δ	315	353	60	63	7.5	15	D	21.8

▲ Stock △ Order

Spare Parts


Diameter	Insert	Kni fe-hol de r	Block	clamping screw	knife-holder screw	Wrench
ØD		11-1				
Ø80-Ø315		LSE12R/L	MO4D#	DMOUGAY	LOMENAEA	S3
Ø80-Ø315	SE□N1504	LSE15R/L	W01R/L	DM8×21X	LOM5×15.1	S4
	•					•

Face Milling tool









Type of Milling Tools

	_	Sto	ck	Dimension (mm)						Adapter	Weight
	Туре	R	L	ØD	ØD1	ød	ød L		Z	11dupter	(kg)
FMA04	-050-A22-OF05-04	•	Δ	50	56	22	40	3.5	4	Α	0.3
	-050-A22-OF05-05	Δ	Δ	50	56	22	40	3.5	5	Α	0.4
	-063-A22-OF05-05	A	Δ	63	69	22	40	3.5	5	Α	0.5
	-080-A27-OF05-06	A	Δ	80	86	27	50	3.5	6	Α	0.8
	-100-B32-OF05-07	A	Δ	100	106	32	50	3.5	7	В	1.2
	-125-B40-OF05-08	A	Δ	125	130	40	63	3.5	8	В	2.7
	-160-B40-OF05-10	A	Δ	160	165	40	63	3.5	10	В	5.1
	-160-C40-OF05-10	Δ	Δ	160	165	40	63	3.5	10	С	4.1

▲Stock △Order


Spare Parts

Discourse	Insert	insert screw	Wrench
Diameter ØD			
Ø50- Ø63	OFKT05T3	L60M4×10	T15
Ø80 -Ø160	OFKT05T3	L60M4×10	T15T

Face Milling tool Kr:45°







Type of Milling Tools

	_	Sto	ck	Dimension (mm)				Tooth	Adapter	Weight	
	Type	R	L	ØD	ØD1	ød	L	a _p max	Z	Muapter	(kg)
FMA04	-125-B40-OF07-08	•	Δ	125	136	40	63	5	8	В	3.9
	-160-B40-OF07-10	•	Δ	160	171	40	63	5	10	В	5.9
	-200-C60-OF07-12	•	Δ	200	211	60	63	5	12	С	7.6
	-250-C60-OF07-16	•	Δ	250	261	60	63	5	16	С	13.3
	-315-D60-OF07-20	A	Δ	315	321	60	63	5	20	D	20.3

▲ Stock △ Order


Spare Parts

Diameter	Applicable Insert	Kni fe-hol der	Block	clamping screw	knife-holder screw	Wrench
ØD ØD			4			
Ø125-Ø315		LOF07R/L	W02R/L	DM8×21X	LOM5×15.1	\$3 \$4
	OFKR0704					

Face Milling tool







Type of Milling Tools

		Sto	ock		Din	nension	(mm)		Tooth	Installation disk	Weight
	Type	R	L	ØD	ØD1	ød	L	apmax	Z	Number	(kg)
FMA05	-200-C60-SN12-18	Δ	\triangle	200	215	80	40	5	18	Adapter1	6.9
	-250-C60-SN12-24	Δ	Δ	250	265	120	40	5	24	Adapter2	9.4
	-315-D60-SN12-30	Δ	Δ	315	330	180	40	5	30	Adapter3	12.5
	-355-D60-SN12-34	Δ	Δ	355	370	220	40	5	34	Adapter4	15.1
	-400-D60-SN12-38	Δ	Δ	400	415	250	40	5	38	Adapter5	18.4
	-450-D60-SN12-44	Δ	Δ	450	465	300	40	5	44	Adapter6	21.7
	-200-C60-SN15-18	Δ	Δ	200	220	80	40	5.5	18	Adapter1	6.9
	-250-C60-SN15-24	Δ	Δ	250	270	120	40	5.5	24	Adapter2	9.4
	-315-D60-SN15-30	Δ	Δ	315	335	180	40	5.5	30	Adapter3	12.6
	-355-D60-SN15-34	Δ	Δ	355	375	220	40	5.5	34	Adapter4	15.2
	-400-D60-SN15-38	Δ	Δ	400	420	250	40	5.5	38	Adapter5	18.4
	-450-D60-SN15-44	Δ	Δ	450	470	300	40	5.5	44	Adapter6	21.8

▲ Stock △ Order

Spare Parts

Diameter	Insert	Block	clamping screw	Wrench
ØD		615		
Ø200-Ø450	SNKN1204	W04N	DM8×21X	0.4
Ø200-Ø450	SNKN1504	W05N	DIVIO*21X	S4


■ The Installation disk Specification of FMA 05

Installation					Dim	ensi	on (n	nm)					
Installation	Type	ØD	Ød	Ød1	Ød2	Ødз	Ød4	Ød5	ØС	ØC1	ØC2	N	刀具ØD
ØC2	Adapter1	180	60	26	18	_	_	80	120	101.6	_	4	Ø200
ØC1	Adapter2	230	60	26	18	-		120	170	101.6	-	4	Ø250
25.4	Adapter3	290	60	26	18	32	22	180	230	101.6	177.8	6	Ø315
40 57	Adapter4	330	60	26	18	32	22	220	270	101.6	177.8	6	Ø355
N-bolt 14 ød1 ød3 ød5	Adapter5	370	60	26	18	32	22	250	300	101.6	177.8	6	Ø400
ØC ØD	Adapter6	420	60	26	18	32	22	300	350	101.6	177.8	6	Ø450

Face Milling tool Kr:45°







Type of Milling Tools

	m.	Sto	ock		Din	nension	(mm)		Tooth	Adapter	Weight
	Туре	R	L	ØD	ØD1	ød	L	apmax	Z	Huapter	(kg)
FMA07	-050-A22-ON06-05	A	Δ	50	62	22	40	4	5	А	0.3
	-063-A22-ON06-06	A	Δ	63	75	22	40	4	6	Α	0.5
	-080-B27-ON06-07	A	Δ	80	92	27	50	4	7	В	1.0
	-100-B32-ON06-08	A	Δ	100	112	32	63	4	8	В	1.9
	-125-B40-ON06-09	A	Δ	125	137	40	63	4	9	В	3.5
	-160-C40-ON06-11	A	Δ	160	172	40	63	4	11	С	4.3
	-200-C60-ON06-13	A	Δ	200	212	60	63	4	13	С	6.4
	-250-C60-ON06-15	A	Δ	250	262	60	63	4	15	С	13.4
	-315-D60-ON06-17	A	Δ	315	327	60	80	4	17	D	21.9
	-063-A22-ON08-05	A	Δ	63	78	22	40	5	5	Α	0.5
	-080-B27-ON08-06	A	Δ	80	95	27	50	5	6	В	0.9
	-100-B32-ON08-07	A	Δ	100	115	32	63	5	7	В	1.8
	-125-B40-ON08-08	A	Δ	125	140	40	63	5	8	В	3.1
	-160-C40-ON08-10	A	Δ	160	175	40	63	5	10	С	4.1
	-200-C60-ON08-12	A	Δ	200	215	60	63	5	12	С	6.1
	-250-C60-ON08-12	A	Δ	250	265	60	63	5	14	С	12
	-315-D60-ON08-16	A	Δ	315	330	60	80	5	16	D	21


▲ Stock △ Order

Spare Parts

Diameter		insert screw	Wrench
ØD	Insert		
Ø50 -Ø315	ONHU06□□□□ –PF/PM/W	L60M4×10	T15T
Ø63-Ø315	ONHU08 □□□□ -PF/PM/W	L60M 5×13	Т20Т

Face Milling tool Kr:45°





Type of Milling Tools

	Type	Sto	ock		Tooth	Weight					
Турс		R	L	ØD	ØD1	ød	L	L ₁	apmax	Z	(kg)
	-025-XP20-ON06-02	A	Δ	25	37	20	95	45	4	2	0.2
	-040-XP25-ON06-03	•	Δ	40	52	25	106	50	4	3	0.4
	-032-XP25-ON08-02	A	Δ	32	47	25	111	55	5	2	0.4
	-040-XP25-ON08-03	•	Δ	40	55	25	111	55	5	3	0.5
	-050-XP25-ON08-04	A	Δ	50	65	25	111	55	5	4	0.6

\triangle Stock \triangle Order

Spare Parts


Diameter		insert screw	Wrench
ØD	Insert		
Ø25 - Ø40	ONHU06□□□□ –PF/PM/W	L60M4×10	T15T
Ø32-Ø50	ONHU08 □□□□ -PF/PM/W	L60M 5×13	Т20Т

Face Milling tool Kr:45°









Type of Milling Tools

	Т	Sto	ock		Din	ension	(mm)		Tooth	Adapter	Weight
	Type	R	L	ØD	ØD1	ød	L	apmax	Z	Traupter	(kg)
FMA08	-050-A22-SE13-03	•	Δ	50	61	22	40	6	3	А	0.3
	-063-A22-SE13-04	•	Δ	63	74	22	40	6	4	А	0.5
	-080-A27-SE13-04	•	Δ	80	91	27	50	6	4	А	1.2
	-100-B32-SE13-05	A	Δ	100	107	32	50	6	5	В	1.2
	-125-B40-SE13-06	A	Δ	125	136	40	63	6	6	В	2.6
	-050-A22-SE13-04	•	Δ	50	61	22	40	6	4	А	0.3
	-063-A22-SE13-05	•	Δ	63	74	22	40	6	5	А	0.5
	-080-A27-SE13-06	•	Δ	80	91	27	50	6	6	Α	1.2
	-100-B32-SE13-07	•	Δ	100	107	32	50	6	7	В	1.2
	-125-B40-SE13-08	•	Δ	125	136	40	63	6	8	В	2.6
	-160-B40-SE13-10	•	Δ	160	170	40	63	6	10	В	4.3
	-200-C60-SE13-12	•	Δ	200	210	60	63	6	12	С	7.6
	-250-C60-SE13-14	A	Δ	250	260	60	63	6	14	С	13.5
	-315-D60-SE13-18	Δ	Δ	315	325	60	70	6	18	D	20.8

∆Stock △ Order

Spare Parts


Diameter	Applicable Insert	insert screw	Shim	shim screw	Wrench	Wrench
ØD ØD				Callin		
Ø50 -Ø100	SEET13T3AGEN-JL	L60M3.5×10	_	_	T.15T	_
Ø125-Ø315	SEMT13T3AGSN-JM/JH/FT SEGT13T3AGFN-JP	L60M3.5×10	S13BS	SM5×7XA	T15T	S4
	OLUTIOTOMURN-JF					

Note: The insert is Mitsubishi brand

Face Milling tool Kr:55°







Type of Milling Tools

	Туре	Sto	ock		Dimens	ion (mm)		Tooth	Adapter	Weight
	Туре	R	L	ØD	ød	L	apmax	Z	Adapter	(kg)
FMD02	-080-A27-HN09-08	•	Δ	80	27	50	6	8	Α	1.1
	-100-B32-HN09-10	A	Δ	100	32	63	6	10	В	2.6
	-125-B40-HN09-14	A	Δ	125	40	70	6	14	В	3.7
	-160-B40-HN09-18	A	Δ	160	40	63	6	18	В	5.6
	-200-C60-HN09-22	A	Δ	200	60	63	6	22	С	6.3
	-250-C60-HN09-28	A	Δ	250	60	63	6	28	С	10.3
	-315-D60-HN09-32	A	Δ	315	60	63	6	32	D	21.7


▲ Stock △ Order

Diameter	Applicable Insert	Block	clamping screw	Wrench
ØD				
Ø80-Ø315		W06T	DM6×25	\$3
	HNEX0905			

Face Milling tool Kr: 67°







Type of Milling Tools

		Sto	ock		Dim	ension	(mm)		Tooth	A 1	Weight
	Туре	R	L	ØD	ØD1	ød	L	apmax	Z	Adapter	(kg)
FMD02	-050-A22-PN11-04	A	Δ	50	60.1	22	50	5	4	А	0.6
sparsel y unequally	-063-A22-PN11-05	A	Δ	63	73.1	22	50	5	5	A	0.8
teeth space	-080-B27-PN11-06	A	Δ	80	90.1	27	50	5	6	А	1.1
	-100-B32-PN11-07	A	Δ	100	110.1	32	50	5	7	В	1.8
	-125-B40-PN11-08	A	Δ	125	135.1	40	63	5	8	В	2.9
	-160-B40-PN11-10	A	Δ	160	170.1	40	63	5	10	В	5.6
	-200-C60-PN11-12	A	Δ	200	210.1	60	63	5	12	С	7.9
	-250-C60-PN11-14	A	Δ	250	260.1	60	63	5	14	С	13.4
densely	-050-A22-PN11-05	A	Δ	50	60.1	22	50	5	5	Α	0.6
Toothed	-063-A22-PN11-06	A	Δ	63	73.1	22	50	5	6	А	0.9
	-080-B27-PN11-08	A	Δ	80	90.1	27	50	5	8	Α	1.2
	-100-B32-PN11-10	A	Δ	100	110.1	32	50	5	10	В	1.9
	-125-B40-PN11-12	A	Δ	125	135.1	40	63	5	12	В	3.2
	-160-B40-PN11-14	A	Δ	160	170.1	40	63	5	14	В	6.4
	-200-C60-PN11-16	A	Δ	200	210.1	60	63	5	16	С	8.5
	-250-C60-PN11-18	A	Δ	250	260.1	60	63	5	18	С	18.0
	-315-D60-PN11-26	A	Δ	315	325.1	60	80	5	26	D	24.5

▲ Stock △ Order


Spare Parts

Diameter		insert screw	Wrench
ØD	Insert		
Ø50 -Ø315	PNEG110512R-CR		
	PNEG110512R-CM	L60M4×10	T15T

Face Milling tool







Type of Milling Tools

Type		Sto	ck		Dim	ension	(mm)		Tooth	Adapter	Weight
		R	L	ØD	ØD1	ød	L	a _p max	Z	Auapter	(kg)
	-080-A27-PN11-10	A	Δ	80	90.1	27	50	5	10	Α	1.3
	-100-B32-PN11-14	•	Δ	100	110.1	32	50	5	14	В	1.6
	-125-B40-PN11-18	A	Δ	125	135.1	40	63	5	18	В	3.2
	-160-B40-PN11-22	A	Δ	160	170.1	40	63	5	22	В	5.8


▲ Stock △ Order

Diameter			clamping screw	Wrench
ØD	Insert	Block		
	PNEG110512R-CR	W4 ON	DMCv20A	00
Ø80-Ø160	PNEG110512R-CM	W18N	DM6×20A	S3

Face Milling tool Kr:60°







Type of Milling Tools

,	Type			Di	imensio	n (mm)		Tooth	Adapter	Weight
- 7P*		Stock	ØD	ØD1	ød	L	apmax	Z	Mapter	(kg)
FMD03	-125-B40-LN25-05	Δ	125	154	40	63	17	5	В	4.5
	-160-C40-LN25-06	Δ	160	189	40	63	17	6	С	6.9
	-200-C60-LN25-08	•	200	229	60	70	17	8	С	10.5
	-250-C60-LN25-10	•	250	278	60	70	17	10	С	16.7
	-315-D60-LN25-12	•	315	346	60	80	17	12	D	27.3
	-400-D60-LN25-16	•	400	427	60	80	17	16	D	47.1


▲ Stock △ Order

Spare Parts

D: .	Applicable Insert	shim screw	Shim	insert screw	Wrench		
Diameter ØD	•		5	S. Tilling		>	
Ø125-Ø315	LNKT2007	L60M3×8	LLN20R-ZR	L60M4×15	T15T	T08	
Ø125-Ø400	LNKT2510	L60M3.5×10	LLN25R-ZR	L60M5×17	Т20Т	T15	

Face Milling tool Kr:75°





Type of Milling Tools


	_	Sto	ock		Din	ension	(mm)		Tooth Adapter		weight (kg)
Type		R	L	ØD	ØD1	ød	L	apmax	Z	Auaptei	
FME01	-125-B40-LN15-16	Δ	Δ	125	132	40	63	8	16	В	3.5
	-160-B40-LN15-20	Δ	Δ	160	168	40	63	8	20	В	6.1
	-200-C60-LN15-25	Δ	Δ	200	208	60	63	8	25	С	7.4
	-250-C60-LN15-32	Δ	Δ	250	257	60	63	8	32	С	13.1
	-315-D60-LN15-40	Δ	Δ	315	323	60	70	8	40	D	25.5

▲ Stock △ Order

Diameter	Insert	insert screw	Wrench		
ØD ØD		30mm			
Ø125-Ø315		L90M4×11	T15T		
	LNE32.534				

Face Milling tool Kr:75°





Type of Milling Tools


	Type			Dia	mension	(mm)		Tooth	Adapter	Weight
1,766		Stock	ØD	ØD1	ød	L	apmax	Z	Adapter	(kg)
FME02		Δ	50	54	22	40	6	4	А	0.3
	-063-A22-SP12-05		63	66	22	50	6	5	Α	0.6
	-080-A27-SP12-06		80	83	27	50	6	6	A	0.9
	-100-B32-SP12-07	Δ	100	103	32	50	6	7	В	1.4
	-125-B40-SP12-08		125	128	40	63	6	8	В	2.5

△Order **▲** Stock

Spare Parts

Diameter	Applicable Insert	insert screw	Wrench
ØD		a min	
Ø50-Ø125	SPKW1204	L60M5×14	Т20Т
	SPKT1204		





Type of Milling Tools

		Sto	ock		Dim	ension	(mm)		Tooth	Adapter	Weight
,	Type		L	ØD	ØD1	ød	L	apmax	Z	Adapter	(kg)
FME03	-080-A27-SP12-04	•	Δ	80	84	27	50	6	4	А	1.1
	-100-B32-SP12-06	A	Δ	100	104	32	50	6	6	В	1.9
	-125-B40-SP12-08	A	Δ	125	129	40	63	6	8	В	3.5
	-160-B40-SP12-10	A	Δ	160	164	40	63	6	10	В	5.7
	-200-C60-SP12-12	A	Δ	200	203	60	63	6	12	С	8.2
	-250-C60-SP12-16	A	Δ	250	253	60	63	6	16	С	13.8
	-315-D60-SP12-20	A	Δ	315	318	60	70	6	20	D	23.5
•	-080-A27-SP15-04	A	Δ	80	84	27	50	8	4	Α	1.0
	-100-B27-SP15-06	A	Δ	100	104	27	50	8	6	В	1.8
	-125-B40-SP15-08	A	A	125	129	40	63	8	8	В	3.3
	-160-B40-SP15-10	A	A	160	164	40	63	8	10	В	5.4
	-200-C60-SP15-12	A	A	200	204	60	63	8	12	С	7.9
	-250-C60-SP15-16	A	A	250	253	60	63	8	16	С	13.6
	-315-D60-SP15-20	A	A	315	318	60	70	8	20	D	23.1

▲Stock △Order

Diameter ØD	Insert	Knife-holder	Block	Clamping	knife-holder screw	Wrench	
			4				
Ø80 - Ø100	ODKN4000	L CD40D#	MOAD/I	WM8×17		\$3 \$4	
Ø125-Ø315	SPKN1203	LSP12R/L	W04R/L	WM8×22	LOM5×15.1		
Ø80-Ø315	SPKN1504	LSP15R/L	W04R/L	WM8×22			